



RECOMMENDED SPACING:



- TRA0601 RUNNERS EVERY 0.3 m OR 1 ft.
- TRA1906 CORD GUIDES EVERY 2 m OR 6.5 ft.
- SUSPENSION EVERY 1.5 m OR 5 ft.



THIRD ANGLE PROJECTION



METHOD OF ROPE CLAMPING



Triple E Ltd
13A AIRPORT IND. EST.
WIRELESS ROAD
BIGGIN HILL
KENT
TN16 3BW
TEL: +44 (0) 1959 570333
WWW.TRIPLEE.LTD

THE CONTENTS OF THIS DRAWING CONSTITUTES
DESIGN COPYRIGHT AND MAY NOT BE
REPRODUCED OR DISCLOSED TO A THIRD PARTY
WITHOUT PRIOR WRITTEN PERMISSION FROM
TRIPLE E LTD

ALL DIMENSIONS IN MILLIMETERS (mm)
UNLESS STATED OTHERWISE
GENERAL TOLERANCES TO FOLLOW ± 0.2

TITLE

**SIDE CORDED WITH INDEPENDENT
MASTER CARRIERS FOR ONE CURTAIN
VIEWED FROM UNDERSIDE**

DRAWING No.

UBM-CD14

REV

2

SPECIAL INSTRUCTIONS

SUSPENSION METHOD NOT SHOWN.

DRAWN BY:

DS

APPROVED BY:

SCALE:

NTS

DATE:

15/06/2026

DATE:

SHEET SIZE:

A3